

EL-Link

Model name	EL-IPC2FUCO-BUDL30-FL28MIC-ECO
Design	
Video	
Imaging Device	1/3"
Effective Pixels	2MP 1920(H)×1080 (V)
Scanning System	Progressive CMOS
Min. Illumination	Color 0.008lux @ F1.6(AGC ON) ; B/W 0 lux @ IR ON
Lens Type	
Focal Length (Zoom Ratio)	2.8 mm
Max. Aperture Ratio	F No. 2.0
Angular Field of View	Horizontal:97° , Vertical:53° , Diagonal: 115°
Min. Object Distance	1.8m
Lens Type	Fixed(M12)
Operational	
IR LED	1
WarmLight	1
IR Viewable Length	Up to 25m
WarmLight Viewable Length	Up to 20m
Type of complementary light	Default warm light, switchable infrared light
Motion Detection	Off/On (8 Level)
Wide Dynamic Range	DWDR
Digital Noise Reduction	3D DNR
Image Setting	Full Color Mode/Day&Night Mode/Smart Illumination
White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
On-Board Storage	NA
Alarm	NA
Audio	Built-in microphone
P2P	NA
Hardware Reset	NA
Smart Feature	SMD(Pedestrian & Vehicle) , Line Crossing , Intrusion, Region Entrance, Region Exiting
Defog	YES
Network	
Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264
Resolution	Main Stream@30fps 2MP(1920x1080) 720p(1280x720) Sub Stream@30fps
Video Quality Adjustment	512Kbps ~ 4Mbps
Bitrate control method	CBR/VBR
P2P	NA

IP	IPv4
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,HTTPS
Security	complicated password;Authenticated username and password
Application Programming Interface	ONVIF
Web Viewer	IE10/11
Environmental	
Operating Conditions	-35 ~ +55°C/less than 90% RH
Ingress Protection	IP66
Electrical	
Input Voltage / Current	POE(IEEE802.3af)
Power Consumption	PoE (48V) : max 3.05W
Mechanical	
Material	Plastic